



PRODUCT DATA SHEET

LINEHAUL EXPRESS

Linehaul Express is a modern high powered Diesel Engine Oil specifically formulated to meet the demanding requirements of the CI-4(Compression Ignition, four cycle) specification.

Environmental Protection Agencies around the world have been the driving force for change to diesel engine oil specifications. EPA regulations requiring reductions in exhaust gas emissions has forced engine manufacturers to redesign engines to meet more stringent emission standards.

Typically, reduction of nitrous oxide emissions 50% below the 1998 limits forced engine redesigns calling for higher cylinder pressures, increased piston ring zone temperatures and Exhaust Gas Recirculation (EGR). These engine redesigns have added to the stresses on the lubricant.

Principally there are 16 engine and bench tests in this category, four new tests were added using the Cummins M-11 with EGR and the Mack T10 which address wear issues associated with the EGR technology, Caterpillar 1R is a new test for piston deposits and the elastomer compatibility test was added to ensure seal compatibility with the CI-4 oils.

Linehaul Express provides maximum protection for line haul and off road vehicles operating in arduous conditions. Linehaul Express is recommended for naturally aspirated and turbo charged diesel engines providing the best anti-wear, dispersant and detergent technology available internationally from a multi-function lubricant package.

Linehaul Express also has the capability of extended drain intervals in accordance with the recommendations of the individual engine builders for their specific engines.

TYPICAL PROPERTIES

Density @ 15°C ATSM D4052	0.883
Viscosity @ 40°C (cSt) ATSM D445	110.0
Viscosity @ 100°C (cSt) ASTM D445	14.8
Viscosity Index ASTM D2270	>140
Pour Point (°C)	-30 (Max)
Open Flash Point (°C)	200
Ash (%mass)	≤1.0
TBN	11

PERFORMANCE SPECIFICATIONS

API: CI-4/CH-4/SL

ACEA: E7-16

JASO: DH-1

MB-Approval 228.3

VOLVO: VDS-3

CAT: ECF-2, ECF-1-A

RVI: RLD/RLD-2

DETROIT DIESEL: DDC 93K215

SAE: 15W-40

GLOBAL: DHD-1

MACK: EO-N, EO-M Plus

MAN M: 3275

CUMMINS: CES 20076/77/78

MTU: Type 2

DEUTZ: DQC 111-10

All reasonable care has been taken in the preparation of the advice and information contained herein and is correct at the time of preparation; no liability whatsoever is accepted for any loss or damage because of the use of such advice and information contained herein. Buyers should always determine the suitability of products for their particular purpose. The information provided is a guide to industry and is not necessarily manufacturing specifications which vary from time to time.

