



PRODUCT DATA SHEET

LITHPLEX TACKY

LITHPLEX TACKY is a high performance, lithium complex, multi-purpose grease possessing superior lubrication characteristics for a wide range of anti-friction and plain bearings, gears and couplings in automotive, marine, agricultural and industrial applications.

The addition of rust, oxidation and corrosion inhibitors combined with a very effective extreme pressure additive makes LITHPLEX TACKY the choice for all of your multi-purpose applications.

Automotive recommendations include cars, trucks, tractors, trailers, for chassis, universal joints and wheel bearings particularly those in vehicles fitted with disc brakes where high temperatures cause ordinary greases to soften and give ineffective lubrication.

In industrial applications suitable for ball, roller, needle and slow speed plain bearings operating under all service conditions.

PRODUCT BENEFITS:

- High and low temperature applications
- Protects against shock loadings
- Prevents scuffing
- Excellent shear stability
- Wear reduction resulting in longer service life.

TYPICAL PROPERTIES

NLGI	#2
NLGI Service Category	GC-LB
Thickener Type	Lithium complex
Colour	Blue
Texture	Tacky
Worked penetration @ 25°C (dmm; after strokes)	265-295
Dropping point (°C)	290
Four Ball Weld Load (kg)	315
Base oil viscosity @ 40°C	220
Operating Temperature (°C)	-10 to 180

All reasonable care has been taken in the preparation of the advice and information contained herein and is correct at the time of preparation; no liability whatsoever is accepted for any loss or damage as a consequence of the use of such advice and information contained herein. Buyers should always determine the suitability of products for their particular purpose. The information provided is a guide to industry and is not necessarily manufacturing specification which varies from time to time.