



PRODUCT DATA SHEET

SUPER ON FARM

A true universal lubricant, SUPER ON FARM is formulated as a Super Tractor Oil Universal (STOU) for diesel and four stroke petrol engines, transmissions, final drive, wet brake, clutch, hydrostatic, power steering and hydraulic units. SUPER ON FARM is a multifunctional oil of the highest quality for many applications including all tractor types, combine harvesters, crop sprayers and selected construction and materials handling equipment. SUPER ON FARM is a high-performance oil, blended to give unrivaled protection against wear, rust and corrosion. SUPER ON FARM offers balanced friction performance, giving precise clutch and brake operation.

PRODUCT BENEFITS:

- A single oil to avoid misapplication
- A reduction in inventory costs
- Widely applicable for agricultural equipment
- Provides a quiet responsive tractor for operator comfort
- Increase in hardware and equipment longevity
- More uptime allowing equipment to work harder for longer

TYPICAL PROPERTIES

Density @ 15°C ATSM D4052	0.88
Viscosity @ 40°C (cSt) ATSM D445	110.0
Viscoisty @ 100°C (cSt) ASTM D445	15.6
Viscosity Index ASTM D2270	150
Pour Point (°C)	-30 (Max)
Closed Flash Point (°C)	225
Appearance	Clear & Bright

PERFORMANCE SPECIFICATIONS

SAE: 15W-40
 ACEA: E2 (E7 Level of Soot Control)
 API: CG-4, CF-4, CF, CE/SF
 API: GL-4
 Allison: C-4
 Case-IH: MS 1207
 Caterpillar: TO-2
 Ford: M2C-159B
 John Deere: JDM J7 (Specification Obsoleted 2005)
 MAN: 271
 MB-Approval: 227.1, 228.1, 228.3
 Massey Ferguson: CMS M1139, M1144, M1145
 MIL-L-2104D
 ZF: TE-ML 06B, 06C, 06D, 07B

All reasonable care has been taken in the preparation of the advice and information contained herein and is correct at the time of preparation; no liability whatsoever is accepted for any loss or damage as a consequence of the use of such advice and information contained herein. Buyers should always determine the suitability of products for their particular purpose. The information provided is a guide to industry and is not necessarily manufacturing specification which varies from time to time.