

## TABLEWAY 68 & 220

TABLEWAY fluid is a quality Group II mineral oil developed especially for the slideways of machine tools, planners, lathes and the slides and guideways of other machines

TABLEWAY is suitable for use with the latest high precision machine tools requiring a tacky, non-corrosive extreme pressure lubricant.

**Product Benefits include:**

- High thermal and chemical stability
- High load capacity
- Low coefficient of friction
- Good water demulsibility
- Excellent anti-stick-slip properties
- Excellent wear and corrosion protection
- Improved system efficiency

TABLEWAY 68 is intended for horizontal slide lubrication.

TABLEWAY 220 is intended for vertical slide lubrication.

**TABLEWAY MEETS REQUIREMENTS OF:**

ISO 12925-1/ ISO 6743-6 CKC

ISO 11158/ ISO 6743-4 HM/ HG

ISO 19378/ ISO 6743-13 GA/ GB

DIN CGLP

**TYPICAL PROPERTIES**

ISO	68	220
Density @ 15°C	0.880	0.898
Viscosity @ 40°C (cSt)	61.2-74.8	198-242
Viscosity @ 100°C (cSt)	8.5-9.5	18-20
Viscosity Index	95-105	95-105
Closed Flash Point (°C)	220	255
Appearance	Bright & Clear	Bright & Clear

All reasonable care has been taken in the preparation of the advice and information contained herein and is correct at the time of preparation; no liability whatsoever is accepted for any loss or damage as a consequence of the use of such advice and information contained herein. Buyers should always determine the suitability of products for their particular purpose. The information provided is a guide to industry and is not necessarily manufacturing specification which varies from time to time.