



PRODUCT DATA SHEET

TRUCK & FARM GREASE

Truck & Farm Grease is a heavy-duty premium grease for lubricating heavily loaded gear teeth, bearings, pins, swing gears and ball joints operating under high load and/or high temperature conditions found in such industries as mining, quarries, heavy plant machinery, and transport. Truck & Farm is fortified using the latest polymer technology and utilizes extreme pressure, anti-wear, anti-oxidant, and corrosion inhibiting additives, to give exceptional performance. It provides extended lubrication intervals, especially under arduous conditions and at high operating temperatures. This highly adhesive grease also provides excellent sealing properties against ingress of moisture, dirt, and dust, resulting in extended component life.

FEATURES:

- Exceptional mechanical stability allowing for extended relubrication intervals
- Excellent oxidation stability provides lasting lubrication at high temperature
- Excellent load bearing properties and anti-wear performance
- Good corrosion resistance protects components operating in wet and arduous conditions
- Based on high viscosity mineral oil giving robust film strength at low speeds
- Excellent sealing properties to reduce damage caused by ingress of dirt and dust

TYPICAL PROPERTIES

Appearance	-	Smooth grease
Colour	-	Red
NLGI classification	-	2
Thickener	-	Lithium complex
Base oil	-	Refined mineral oil
Base oil Viscosity @ 40 (cSt)	-	500
Worked penetration	IP50	265-295
Dropping point (°C)	IP132	260 min
Copper corrosion	IP112	Pass
Water washout @ 39°C (%)	ASTM D1264	3
Four ball weld load (kgs)	IP 239	500 min
Operating temperature range	-	-10°C to 150°C

All reasonable care has been taken in the preparation of the advice and information contained herein and is correct at the time of preparation; no liability whatsoever is accepted for any loss or damage as a consequence of the use of such advice and information contained herein. Buyers should always determine the suitability of products for their particular purpose. The information provided is a guide to industry and is not necessarily manufacturing specification which varies from time to time.

