

TURBO ELITE

TURBO ELITE 20W-50 is blended with the finest quality mineral base oils and the highest quality additive materials to provide the user with the best protection for the extensive range of vehicles requiring this viscosity grade.

TURBO ELITE delivers superior engine cleanliness and wear protection while providing reduced sludge formation resulting in an extensive proven history of satisfactory use.

TURBO ELITE has been formulated using higher zinc technology for the protection of flat tappet cams in cars running on unleaded fuel. Viscosity modifiers maintain fluidity during cold temperature start up to protect critical bearing surfaces through rapid circulation.

TURBO ELITE is recommended for use in older passenger cars, utilities, vans, and light truck operations under manufacturers recommended oil drain intervals.

TYPICAL PROPERTIES

Density @ 15°C	0.880
Viscosity @ 40°C (cSt)	157
Viscosity @ 100°C (cSt)	18.1
Viscosity Index	128
Cold Crank Viscosity (cP@-15°C)	5900
Closed Flash Point (°C)	230
Sulphated Ash (%mass)	<1.3
Phosphorus (%mass)	0.09
Zinc (%mass)	0.110
Calcium (%mass)	0.260
TBN	11.1

PERFORMANCE SPECIFICATIONS

SAE: Viscosity 20W-50

API: SL/CF

JASO T903:2011 (Performance Level)

SUITABLE FOR OBSOLETE SPECIFICATIONS

ACEA A2, B2, CCMC PD-2

VW 500.00/501.01 Pre 1999

PSA B71 2295 Pre 1998

FORD M2C-153E

GM HN 2314

All reasonable care has been taken in the preparation of the advice and information contained herein and is correct at the time of preparation; no liability whatsoever is accepted for any loss or damage as a consequence of the use of such advice and information contained herein. Buyers should always determine the suitability of products for their particular purpose. The information provided is a guide to industry and is not necessarily manufacturing specification which varies from time to time.